

Typ	Skl. číslo	MC	vlnová délka	barva	lv	při If	vyzař. úhel	Vftyp	pouzdro
LED 5MM BLIK GREEN 1500/20°	511-577	8,90	568 nm	zelená, blikací	1500 mcd	20 mA	20°	2,1 V	H5,0
LED 5MM BLIK PURE GREEN 8000/20°	511-563	16,50	525 nm	zelená, blikací	2,4 Hz 8000 mcd	20 mA	20°	3,3 V	H5,0
LED 5MM BLIK RED 3500/20°	511-576	8,90	635 nm	červená	3600 mcd	20 mA	20°	2,0 V	H5,0
LED 5MM BLIK YELLOW 4000/20°	511-736	8,90		žlutá, blikací				3,3 V	
LED 5MM BLUE 4500/80°	511-798	24,00	465–475 nm	modrá	2800–4700 mlm	100 mA	70–90°	3,5–4,0 V	
LED 5MM BLUE 1100/60° CREE	511-760	11,00	460nm	modrá, čirá	550–1100 mcd		55–65°	3,3 V	
LED 5MM BLUE 200/150°	511-700	5,00	470 nm	modrá, čirá	200 mcd		150°	3,2 V	
LED 5MM BLUE 2300/30°	511-783	6,90	465–475 nm	modrá	1520–3000 mcd	20 mA	24–30°	2,8–3,4 V	
LED 5MM BLUE 2300/40°	511-564	6,90	470 nm	modrá	2300 mcd	20 mA	40°	3,3 V	H5,0
LED 5MM BLUE 3000/20°	511-144	6,90	470 nm	modrá, čirá	2000 mcd	20 mA	30°	3,5 V	P5,0
LED 5MM BLUE 3000/40° CREE	511-759	9,00	460 nm	modrá, čirá	1500–3000 mcd		30–40°	3,3 V	
LED 5MM BLUE 400/60° DIFF	511-749	4,50	470 nm	modrá, difuzní	200–400 mcd		55–65°	3,3 V	
LED 5MM BLUE 4000mcd/12°	511-391	22,00	470 nm	modrá čirá	4000 mcd	30 mA	12°		
LED 5MM BLUE 4500/10°	511-565	6,90	470 nm	modrá	4500 mcd		10°	3,3 V	H5,0
LED 5MM BLUE DARK 2000/30°	511-873	5,00	450–460 nm	tmavě modrá	1000–2000 mcd	20 mA	24–30°	2,8–3,4 V	
LED 5MM BLUEGREEN 4200/40° CREE	511-758	12,90	505 nm	modrozelená	2200–4200 mcd		35–45°	3,3 V	
LED 5MM BLUEGREEN 4500/40°	511-596	12,00	500 nm	modrozelená, čirá	4500 mcd		40°	3,3 V	H5,0
LED 5MM BLUEGREEN 550/150°	511-896	6,50	500–510 nm	modrozelená	280–550 mcd		130–170°	3,0–3,6 V	
LED 5MM BLUEGREEN 8000/20°	511-567	10,00	500 nm	modrozelená	8000 mcd		20°	3,3 V	H5,0
LED 5MM CE UHE	511-404	16,50	630 nm	hyper oranžová	10 000 mcd	20 mA	30°	2,4 V	K5,0
LED 5MM RED POINT	511-258	1,00	700 nm	červená, čirá	30 mcd	20 mA	12°	2,2 V	B5,0-1
LED 5MM CYL.BLUE 300/120°	511-540	8,50	470 nm	modrá	300 mcd	20 mA	120°	3,3 V	H5,0-1
LED 5MM CYL.BLUE 600/120°	511-659	12,50	460 nm	modrá, čirá	600 mcd		120°	3,3 V	
LED 5MM CYL.PURE GREEN 1000/120°	511-541	12,40	525 nm	zelená	1000 mcd	20 mA	120°	3,3 V	H5,0-1
LED 5MM CYL.RED 300/120°	511-542	2,00	635 nm	červená	300 mcd	20 mA	120°	2,1 V	H5,0-1
LED 5MM CYL.RED 450/120°	511-660	3,00	624 nm	červená, čirá	450 mcd		120°	2,1 V	
LED 5MM CYL.RED 900/120°	511-661	6,50	624 nm	červená, čirá	900 mcd		120°	2,1 V	
LED 5MM CYL.WHITE 200/150°	511-692	5,00	7000 K	bílá, čirá	200 mcd		150°	3,3 V	
LED 5MM CYL.WHITE 900/120°	511-543	8,50	7000 K	bílá	900 mcd		120°	3,3 V	H5,0-1
LED 5MM CYL.YELLOW 500/120°	511-579	2,90	588 nm	žlutá	200 mcd		120°	2,0 V	H5,0-1
LED 5MM GREEN	511-060	1,50	568 nm	zelenožlutá, dif.	150 mcd	20 mA	60°	2,1 V	B5,0
LED 5MM GREEN 800/30°	511-874	2,00	567–573 nm	zelená	400–800 mcd	20 mA	24–30°	1,8–2,4 V	
LED 5MM GREEN 800/60° DIFF	511-748	6,90	525 nm	zelená, difuzní	400–800 mcd		55–65°	3,3 V	
LED 5MM ORANGE 4000/20°	511-608	3,50	605 nm	oranžová, čirá	4000 mcd		20°	2,1 V	
LED 5MM OVAL BLUE 400/50/110°	511-695	5,00	470 nm	ovál modrá, čirá	400 mcd		50/110°	3,3 V	
LED 5MM OVAL BLUE 1300/40/100°	511-595	8,90	470 nm	modrá, ovál, čirá	1300 mcd		40/100°	3,3 V	H2,0-2
LED 5MM OVAL BLUE 2300/20/50°	511-537	8,90	470 nm	modrá, ovál	2300 mcd		20/50°	3,3 V	H2,0-2
LED 5MM OVAL PURE GREEN 1400/50/110°	511-694	8,90	525 nm	ovál zelená, čirá	1400 mcd		50/110°	3,2 V	
LED 5MM OVAL PURE GREEN 3000/40/100°	511-593	12,50	525 nm	zelená ovál, čirá	3000 mcd		40/100°	3,3 V	H2,0-2
LED 5MM OVAL PURE GREEN 7000/20/50°	511-538	12,50	525 nm	zelená, ovál	7000 mcd		20/50°	3,3 V	H2,0-2
LED 5MM OVAL RED 1400/40/100°	511-594	2,00	635 nm	červená, ovál, čirá	635 nm		40/100°	2,1 V	H2,0-2
LED 5MM OVAL RED 2100/20/50°	511-808	3,00	621–630 nm	ovál červená	1500–2100 mcd		25–50°	1,8–2,4 V	
LED 5MM OVAL RED 2300/20/50°	511-539	2,00	635 nm	červená, ovál	2300 mcd		20/50°	2,1 V	H2,0-2
LED 5MM OVAL RED 400/50/110°	511-696	3,50	635 nm	ovál červená, čirá	400 mcd		50/110°	2,1 V	
LED 5MM OVAL RED 800/40/70°	511-805	10,00	621–630 nm	ovál červená	400–800 mcd		40–70°	1,8–2,4 V	
LED 5MM OVAL WHITE 4500/20/50°	511-691	5,00	7000 K	ovál bílá, čirá	4500 mcd		20/50°	3,2 V	
LED 5MM OVAL YELLOW 1100/40/70°	511-809	5,00	585–594 nm	ovál žlutá	550–1100 mcd		40–70°	1,8–2,4 V	
LED 5MM PURE GREEN 700/150°	511-697	8,90	525 nm	zelená, čirá	700 mcd		150°	3,2 V	
LED 5MM PURE GREEN 13000/10°	511-571	15,50	525 nm	zelená	13000 mcd		10°	3,3 V	H5,0
LED 5MM PURE GREEN 13000/80°	511-799	24,00	521–530 nm	zelená, čirá	7800–13000 mlm	100 mA	70–90°	3,5–4,0 V	
LED 5MM PURE GREEN 1500/60° CREE	511-757	14,50	525 nm	zelená, čirá	1100–1500 mcd		55–65°	3,3 V	
LED 5MM PURE GREEN 6000/30°	511-778	14,50	521–530 nm	zelená, čirá	4180–8200 mcd		24–30°	2,8–3,3 V	
LED 5MM PURE GREEN 6000/40°	511-550	13,40	525 nm	zelená	6000 mcd		40°	3,3 V	H5,0
LED 5MM PURE GREEN 8000/30°	511-782	9,00	518–527 nm	zelená, čirá	5860–10000 mcd	20 mA	24–30°	2,8–3,4 V	
LED 5MM PURE GREEN 9000/20°	511-434	15,50	525 nm	zelená pravá, čirá	9000 mcd	20 mA	20°	3,0 V	P5,0
LED 5MM PURPLE 1500/40°	511-679	9,00	470/630 nm	purpurová, 2 čipy	1500 mcd		40°	3,5 V	
LED 5MM RED 15000/80°	511-800	24,00	621–630 nm	červená, čirá	10000–17000 mlm	100 mA	70–90°	2,4–2,8 V	
LED 5MM RED 500MCD	511-467	1,50	660 nm	červená, difuzní	80 mcd		110°	2,1 V	
LED 5MM RED 1000/60°	511-454	3,50	635 nm	červená, čirá	1000 mcd		60°	2,1 V	
LED 5MM RED 13000/10°	511-734	6,50	624 nm	červená, čirá	13000 mcd		10°	2,1 V	
LED 5MM RED 1500/40°	511-875	2,90	636–645 nm	červená	800–2000 mcd	20 mA	24–30°	1,8–2,4 V	
LED 5MM RED 200/150°	511-699	3,00	625 nm	červená, čirá	200 mcd		150°	2,1 V	
LED 5MM RED 2000/60°	511-672	3,90	624 nm	červená, čirá	2000 mcd		60°	2,1 V	
LED 5MM RED 200MCD	511-409	1,00	660 nm	červená, difuzní	200 mcd		110°	2,2 V	
LED 5MM RED 2300/30°	511-781	2,50	621–630 nm	červená	1520–3000 mcd	20 mA	24–30°	1,8–2,4 V	
LED 5MM RED 2500/40°	511-534	2,50	635 nm	červená	2500 mcd		40°	2,1 V	H5,0
LED 5MM RED 3500/20°	511-535	2,50	635 nm	červená	3500 mcd		20°	2,1 V	
LED 5MM RED 3500/40°	511-673	3,50	624 nm	červená	3500 mcd		40°	2,1 V	
LED 5MM RED 400/150°	511-745	6,50	625 nm	červená, čirá	200–400 mcd		130–170°	2,2 V	
LED 5MM RED 4000/60°	511-605	5,90	624 nm	červená, čirá	4000 mcd		60°	2,1 V	
LED 5MM RED 4400/30°	511-780	5,90	624–633 nm	červená	3000–5860 mcd	20 mA	24–30°	2,0–2,6 V	
LED 5MM RED 5000/10°	511-452	3,50	635 nm	červená, čirá	5000 mcd		10°	2,1 V	
LED 5MM RED 5000/20°	511-674	3,90	624 nm	červená	5000 mcd		20°	2,1 V	
LED 5MM RED 550/60° DIFF	511-747	3,90	630 nm	červená, difuzní	300–550 mcd		55–65°	2,1 V	
LED 5MM RED 6000/40°	511-606	5,90	624 nm	červená, čirá	6000 mcd		40°	2,1 V	
LED 5MM RED 8000/10°	511-727	3,00	624 nm	červená, čirá	8000 mcd		10°	2,1 V	
LED 5MM RED 8000/20°	511-607	5,90	524 nm	červená, čirá	8000 mcd		20°	2,1 V	
LED 5MM RGB-CA 4000/40°	511-458	24,90	645/525/470 nm	RGB, spol. anoda	4200 mcd		45°	2,1/3,3/3,3 V	
LED 5MM RGB-CC 1000/100	511-846	24,90	635/525/470 nm	RGB, spol. katoda	1000 mcd		100°	2,1/3,3/3,3 V	
LED 5MM RGB-CC 4000/40°	511-155	24,90	635/525/470 nm	RGB, spol. katoda	4600 mcd		45°	2,1/3,3/3,3 V	
LED 5MM ROSE 400/150°	511-897	6,50	470+630 nm	růžová, 2 čipy	200–400 mcd		130–170°	2,8–3,4 V	
LED 5MM WHITE 1100/90°	511-751	5,50	5700–7800 K	bílá, čirá	800–1100 mcd		75–90°	3,3 V	
LED 5MM WHITE 13000/80° WARM	511-901	25,00	5000–10000 K	bílá, teplá	7,8–13 lm	100 mA	70–80°	3,2–3,8 V	
LED 5MM WHITE 13500/15°	511-714	6,00	7000 K	bílá, čirá	13500 mcd		15°	3,3 V	
LED 5MM WHITE 1500/65° CREE	511-770	12,00	7000 K	bílá, čirá	1500 mcd		65°	3,3 V	